

POE ACCESSORIES

Model : POE-SLT



Key Features

- ▶ Input : DC44V~DC57V
- ▶ Output: DC12V/2A
- ▶ Data Speed: 10/100Mbps
- ▶ Power Pin: 1/2(+), 3/6(-) or 4/5(+), 7/8(-)
- ▶ Data Pin: 1236

Model : POE-EXT



Key Features

- ▶ Extended PoE installation range by additional 100m
- ▶ Supports 10/100Mbps data rates
- ▶ Provides 802.3af pwr level when powered by any 802.3at source
- ▶ Provides 802.3at pwr levels when powered by POE-IJT Midspans
- ▶ Extenders can be cascaded to reach up to 500m
- ▶ Plug and play installation

Model : POE-IJT



Key Features

- ▶ Power supply: 30W
- ▶ ACC: Power Core
- ▶ Power Input: 100V~240V
- ▶ Power Output: 56V
- ▶ Power Mode: Mode-A
- ▶ Optional: Mode-B
- ▶ Speed: 1000M
- ▶ PoE Std: IEEE 802.3at

Model : IPEXT-COAX-A (1 PAIR)



Key Features

- ▶ Voltage Range : 12VDC
- ▶ Power Consumption: <1.6W
- ▶ Std Compliance: IEEE 1901
- ▶ Physical speed: 240Mbps
- ▶ Encryption Method: 128-bit AES Encryption

Product Features

1. Long distance transmission up to 2,000m over RG59.
2. RG59 (SYV75-5), TCP/IP Practical Test capacity is :
A.<400M——92Mbps B.<1000M——74Mbps C.<2000M——30Mbps
3. Transmit high-speed data network signal over any pair of two-wire such as CAT5, coaxial cable, power line, telephone line and etc.
4. Support a point-to-point and point to multi-point connection
5. Easy installation, plug and play (PNP) , fast Ethernet connection

