

Model : ND530-10S

3.0MP PoE IR IP Dome Camera



Key Features

- ▶ 1/3" CMOS Sensor
- ▶ 0.07Lux @ F1.2, AGC On
- ▶ DWDR, 3D-DNR
- ▶ Standard HD 2.8mm
- ▶ Metal Casing, Vandal Proof

Technical Specification

Image Sensor	1/3" CMOS Sensor
Effective Pixel	2048 x 1536
Electronic Shutter	1/25 -1/100,000 SEC
Min. Illumination	0.07 Lux@F1.2 (AGC On), 0 Lux IR On
Wide Dynamic Range	Digital WDR
Digital NR	3D-DNR
Day/Night	ICR
Lens Mount / Type	M12 / HD 2.8mm
Video Compression	H.264 / MJPEG
Compression Standard	Baseline/Main/High Profile
Resolution	3MP (2048x1536), 1080p (1920x1080), 720p (1280x720), D1, CIF, 480x240
Main Stream	50Hz : (1~25fps) 3MP/1080p/720p
Bit Rate	128Kbps ~6Mbps
Encode Mode	VBR/CBR
Quality	5 Levels under VBR Freely adjustable under CBR
ROI	3 ROI

Remote Viewing	IE Browsing, CMS Remote Control
Online Connection	Support simultaneous monitoring for up to 4 users ; Support multi-stream real time transmission
Network Protocol	TCP/IP, UDP, DHCP, NTR, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF
Smart Alarm	Motion Alarm
IR LED	10pcs SMD Leds
Power Voltage	DC12V / PoE (<4.5W IR On)
Working Temperature	-20°C ~ +50°C
Working Humidity	10%~90%
Dimension	4.6" x 6.1" (Ø116mm x 91mm)
Net weight	320G

Product Structure

