

Model : NW540-24

4.0MP PoE IR IP Bullet Camera



Key Features

- ▶ 1/3" CMOS Sensor
- ▶ 0.05Lux @ F1.2, AGC On
- ▶ WDR, 3D-DNR
- ▶ Standard HD 3.6mm
- ▶ Metal Casing, IP66

Technical Specification

Image Sensor	1/3" CMOS Sensor
Effective Pixel	2593 x 1520
Electronic Shutter	1/25 -1/100,000 SEC
Min. Illumination	0.05 Lux@F1.2 (AGC On),0 Lux IR On
Wide Dynamic Range	120dB WDR
Digital NR	3D-DNR
Day & Night	ICR
Lens Mount / Type	M12 , HD 3.6mm
Video Compression	H.265/ H.264/ MJPEG Baseline Profile/Main Profile/ High Profile
Resolution	4MP (2592x1440), 2K (2560x1440), 3MP (2304x1296),3MP (2048x1536), 1080p (1920x1080) , 720p (1280x720)
Main Stream	50Hz : (1~25fps) 3MP/1080p/720p/D1/CIF/ 480x240
Bit Rate	128Kbps ~8Mbps
Encode Mode	VBR/CBR
Quality	5 Levels under VBR Freely adjustable under CBR
ROI	3 ROI

Remote Viewing	IE Browsing, CMS Remote Control
Online Connection	4 Online Users
Network Protocol	TCP/IP, UDP, DHCP, NTR, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion Alarm
IR LED	24pcs IR LEDs
Power Voltage	DC12V / PoE (<6.5W IR On)
Working Temperature	-20°C ~+50°C
Working Humidity	10%~90%
Dimension	Ø70mm x 156mm
Net weight	370G

Product Structure

